



# HYTAC® Standard Size Chart



HYTAC materials are available in a wide range of standard and custom sizes.

		HYTAC-W, WF, WFT, FLX, FLXT, C1R, HTF													
		Standard Stock Sizes										Made to order			
Standard Rod Diameter:	in	2.0	2.5	3.0	3.5	4.0	4.5	5.0	5.5	6.0	7.0	8.0	9.0	10.0	12.0
	mm	51	64	76	89	102	114	127	140	152	178	203	229	254	305
12" (305mm) Length												•	•	•	•
24" (610mm) Length		•	•	•	•	•	•	•	•	•	•	•			
Standard Sheet Thickness:	in	1.0	1.5	2.0	2.5	3.0	3.5	4.0	4.5	5.0	6.0				
	mm	25	38	51	64	76	89	102	114	127	152				
24" (610 mm) W x 26" (660mm) L		•	•	•	•	•	•	•	•					•	
24" (610 mm) W x 60" (1524mm) L		•	•	•	•	•	•	•	•	•	•				•

*60" /1524mm: made to order*

		HYTAC B1X® & XTL											
		Standard Stock Sizes										Made to order	
Standard Rod Diameter:	in	2.0	2.5	3.0	3.5	4.0	4.5	5.0	5.5	6.0	7.0	8.0	
	mm	51	64	76	89	102	114	127	140	152	178	203	
12" (305mm) Length		•											
24" (610mm) Length			•	•	•	•	•	•	•	•	•	•	
Standard Sheet Thickness:	in	1.0	1.5	2.0	2.5	3.0	3.5	4.0	4.5				
	mm	25	38	51	64	76	89	102	114				
24" (610mm) W x 24" (610mm) L		•	•	•	•	•	•	•	•				
24" (610mm) W x 48" (1219mm) L		•	•	•	•	•	•						

**Custom-cast or custom-cut sizing available. Contact CMT with requirements**

**Note:** HYTAC-W, WF, WFT, FLX, FLXT, C1R and HTF standard stock tolerances are + 0%, - 1.5% of thickness or diameter HYTAC-XTL, B1X tolerances are + .187" (5mm), - 0.0" (0mm) of thickness or diameter. Length and width tolerances are +/- 0.25" (6.35mm) for all materials.

CUSTOM CUT tolerances are +.125" (3mm), - 0.0" (0mm). CUSTOM CAST tolerances are specified based upon tooling design.